



Bartolomeo

New External Payload Platform on the International
Space Station
Technical Briefing Part 2



DEFENCE AND SPACE



Dr. Christian Steimle
26 February 2019

AIRBUS

Overview to Bartolomeo




- > Concept of Operations
- > Platform Design and Capabilities
- > All-in-one Space Mission Service
- > Capability offered within the UNOOSA cooperation
- > Specific Payload Requirements






What is Bartolomeo?


- > New external platform on ISS / Columbus
- > Able to host all payload sizes
- > Giving best viewing conditions on ISS
- > Providing highest data downlink rate on ISS





Flight
direction

Columbus
Module



Columbus Module

Zenith



Nadir




Payloads


Bartolomeo

Ram

Optical Data Link



ArgUS Multi-Payload Adapter



Columbus Module

Zenith



Nadir




Bartolomeo

Ram

Optical Data Link

Bartolomeo Concept of Operations

Payload Launch



Unpressurized payload launch in
ISS visiting vehicle trunk


[Image credit: NASA]



Pressurized payload launch in ISS
visiting vehicle pressurized compartment

Payload Installation


**Payload installation
by ISS Robotic
Manipulation System**



[Image credit: NASA]

[Image credit: NASA]

Official Use



**Payload transfer
through either ISS
payload airlock**



[Image credit: NanoRacks]

AIRBUS


Payload Retrieval

Payload / sample retrieval option through the payload airlock


[Image credit: NASA]

Bartolomeo Platform Design and Capabilities



Payload Accommodation



Robotic standard interface used for all payload / platform interfaces




Payload Accommodation




ArgUS Multi-Payload Adapter

- ↳ ArgUS can be accommodated on Slot 1, 2, 3, 4, 5, and 6
- ↳ Slot selected based on payload requirements and overall booking situation

Payload Viewing



Slot 3 Zenith View
[image credit: NASA]



Slot 3 Nadir View
[image credit: NASA]




Payload viewing quality

Slots	Nadir	Zenith	Ram
1A	Green	Green	Red
1B	Green	Green	Red
2A	Green	Green	Yellow
2B	Green	Green	Green
3	Green	Green	Green
4	Green	Green	Green
5A	Green	Green	Yellow
5B	Green	Green	Green
6A	Green	Green	Red
6B	Green	Green	Red
7	Red	Green	Green
8	Green	Red	Yellow

Bartolomeo All-in-one Space Mission Service

Bartolomeo All-in-one Space Mission Service

Standard service



Bartolomeo All-in-one Space Mission Service

Optional services

Optional Services

Use of the broadband data downlink


Payload / sample return

Payload design

Payload Return



Broadband Data Downlink



Capability offered within the upcoming 1st Announcement of Opportunity

Capability offered within the upcoming 1st Announcement of Opportunity

- **3U-sized payload** will be integrated, launched, installed and operated as part of the Bartolomeo / ArgUS Multi-Payload Adapter system free of charge
 - ↳ 1U = 10 x 10 x 10 cm
- **Mission duration 1 year** is included

Optional Services:


- Larger payload sizes and longer mission durations are available at 80,000 USD / U / year
- Payload return available at 80,000 USD / kg
- Broadband data downlink capability available at extra charge TBD

SUSTAINABLE DEVELOPMENT GOALS



Specific Payload Requirements

Payload Requirements



General Mission Requirements

ISS Orbit Characteristics

Payload Attitude Characteristics

Payload Design Requirements

Mechanical Interfaces

Electrical Interfaces

Data Interfaces

Software Interfaces

Safety Requirements

Environmental Requirements

Mechanical Environment


Thermal Environment

Electro-magnetic Environment

Space Environment

General Mission Requirements

> ISS orbit characteristics



ISS Orbit Parameter	Value
Orbital inclination	51.64 deg
Orbit altitude	403 to 408 km
Orbital period	92.89 minutes
Solar beta angle variation	-75 to +75 deg
Position error	6 m
Semi-major axis error	20 m




General Mission Requirements

> Payload attitude characteristics

ISS Attitude	Yaw	Pitch	Roll
+XVV +Z Nadir (TEA)	-15° to +15°	-20° to +15°	-15° to +15°
-XVV +Z Nadir	+165° to +195°	-20° to +15°	-15° to +15°
+YVV +Z Nadir	-110° to -80°	-20° to +15°	-15° to +15°
-YVV +Z Nadir	+75° to +105°	-20° to +15°	-15° to +15°
+ZVV -X Nadir	-15° to +15°	+75° to +105°	-15° to +15°
-ZVV -X Nadir	+165° to +195°	+75° to +105°	-15° to +15°


Payload Attitude Parameter	Typical Performance
Attitude rate non-micro-gravity mode	±0.05 deg/s/axis
Attitude knowledge at S0 truss	<0.25 deg/axis (3σ)
Attitude knowledge on Bartolomeo	<1.0 deg/axis (3σ)

On-orbit Vibration Environment




Payload Design Requirements


> Mechanical interfaces



DETAIL A
SCALE 1 : 4




ArgUS Multi-Payload Adapter




- ↳ ArgUS base plate hole pattern to be respected
- ↳ ArgUS soft dock feature to be implemented

Payload Design Requirements

> Mechanical interfaces




ArgUS Multi-Payload Adapter




- ArgUS base plate hole pattern to be respected
- ArgUS soft dock feature to be implemented

Payload Design Requirements

> Electrical and data interfaces



ArgUS Multi-Payload Adapter




ArgUS Interface Parameters

Power (operational)	28 VDC up to 140 W
Power (survival)	28 VDC up to 20 W
Data downlink	0.1 Mbit / s
Commanding and Monitoring	Near Real time through Columbus

Payload Design Requirements

> Safety requirements

Hazard	Control
Structural hazards	<ul style="list-style-type: none"> • Application of factor of safety with positive margin; design for minimum risk • Fault tolerance where applicable • Redundant mechanism
Electrically operated systems	<ul style="list-style-type: none"> • Inhibits to control inadvertent operations appropriate to the hazard level • Redundancy as necessary to perform required functions, Design controls i.e. EMI
Leakage of toxic substances	<ul style="list-style-type: none"> • Fault tolerance in seals appropriate • Structural strength of containers
Flammable materials	<ul style="list-style-type: none"> • Elimination of flammable materials • Containment • Wire sizing and fusing
Pressure systems	<ul style="list-style-type: none"> • Factor of safety
RF systems	<ul style="list-style-type: none"> • Design to have power below hazard level and frequency in approved range • Inhibits to control inadvertent operations appropriate to the hazard level
Battery hazards	<ul style="list-style-type: none"> • Containment • Protection circuits



Environmental Requirements



> Mechanical environment

- ↳ Launch loads for pressurized launch packed in foam
- ↳ On-orbit loads caused by crew handling, airlock operations, robotic operations

> Electro-magnetic environment

> Space environment

- ↳ ATOX environment
- ↳ Plasma environment
- ↳ Radiation environment



Specific Payload Requirements

> **Documentation to be followed:**

- ↳ Bartolomeo User Guide (provided in the AO documentation)
- ↳ ArgUS / Payload Interfaces Definition Document (provided in the AO documentation)

> **Design suggestions:**

- ↳ Tailor your idea to the environment and interfaces
- ↳ Simplify your design as much as possible
- ↳ No pre-qualified hardware expected, qualification will be done through dedicated testing of the integrated hardware

Contact

Dr. Christian Steimle
Program Manager Bartolomeo
Airbus Defence and Space, Bremen, Germany
Email: per-christian.steimle@airbus.com
Mobile: +49 151 277 677 74
<https://de.linkedin.com/in/dr-per-christian-steimle-46217b8a>

Simone Sasse
Key Account Manager International Organizations
Airbus Defence and Space, Ottobrunn, Germany
Email: simone.sasse@airbus.com
Mobile: +49 160 708 56 91
<https://www.linkedin.com/in/simone-sasse-639a46b2>